

◎ POWER RATING

| Engine Speed rpm | Type of Operation | Engine Power | |
|---------------------|----------------------|--------------|-----|
| | | kW | Ps |
| 1500 | Prime Power | 505 | 687 |
| | Standby Power | 555 | 755 |

-. The engine performance is as per GB/T2820.

-. Ratings are based on GB/T1147.1.

---Prime power is available for an unlimited number of hours per year in a variable load application. The permissible average power output over 24 hours of operation shall not exceed 80% of the prime power rating.

---Standby power is available in the event of a utility power outage or under test conditions for up to 200 hours of operation per year. The permissible average power output over 24 hours of operation shall not exceed 80% of the standby power rating.

◎ SPECIFICATIONS

| | |
|------------------------|---|
| ○ Engine Model | SC27G755D2 |
| ○ Engine Type | V-type,4 strokes, water-cooled Turbo charged air-to-air intercooled |
| ○ Combustion type | Direct injection |
| ○ Cylinder Type | Wet liner |
| ○ Number of cylinders | 12 |
| ○ Bore × stroke | 135(5.32) × 155(6.1) mm(in.) |
| ○ Displacement | 26.6(1623) lit.(in3) |
| ○ Compression ratio | 16 : 1 |
| ○ Firing order | 1-12-5-8-3-10-6-7-2-11-4-9 |
| ○ Injection timing | 11.5°BTDC |
| ○ Dry weight | Approx. 2080kg (4585 lb) |
| ○ Dimension (L×W×H) | 1930×1686×1872mm (76×66.4×75.8 in.) |
| ○ Rotation | Counter clockwise viewed from Flywheel |
| ○ Fly wheel housing | SAE NO.0 |
| ○ Fly wheel | SAE NO.18 |

◎ MECHANISM

| | |
|------------------------|---|
| ○ Type | Over head valve |
| ○ Number of valve | Intake 1, exhaust 1 per cylinder |
| ○ Valve lashes at cold | Intake 0.325mm (0.0128 in.) Exhaust 0.375mm (0.0148 in.) |

◎ VALVE TIMING

| | Opening | Close |
|-----------------|--------------|--------------|
| ○ Intake valve | 20 deg. BTDC | 48 deg. ABDC |
| ○ Exhaust valve | 48 deg. BBDC | 20 deg. ATDC |

◎ COOLING SYSTEM

| | |
|------------------|--------------------------------|
| ○ Cooling method | Fresh water forced circulation |
| ○ Water capacity | 48 liters (12.7 gal.) |

◎ FUEL CONSUMPTION

| | |
|---------|--------|
| ○ Power | lit/hr |
| 25% | 37.8 |
| 50% | 66.3 |
| 75% | 95.3 |
| 100% | 126.0 |
| 110% | 139.0 |

◎ FUEL SYSTEM

| | |
|--------------------|---------------------------|
| ○ Injection pump | Yijie in-line “P” type |
| ○ Governor | Electric type |
| ○ Feed pump | Mechanical type |
| ○ Injection nozzle | Multi hole type |
| ○ Opening pressure | 240kg/cm2 (3414 psi) |
| ○ Fuel filter | Full flow, cartridge type |
| ○ Used fuel | Diesel fuel oil |

◎ LUBRICATION SYSTEM

| | |
|--------------------|---|
| ○ Lub. Method | Fully forced pressure feed type |
| ○ Oil pump | Gear type driven by crankshaft |
| ○ Oil filter | Full flow, cartridge type |
| ○ Oil pan capacity | High level 65 liters (17.16 gal.) Low level 55 liters (14.52 gal.) |
| ○ Angularity limit | Front down 25 deg. Front up 35 deg. Side to side 35 deg. |
| ○ Lub. Oil | Refer to Operation Manual |

◎ ENGINEERING DATA

| | |
|-----------------------------|---------------------------|
| ○ Water flow | 740 liters/min @1,500 rpm |
| ○ Heat rejection to coolant | 68 kcal/sec @1,500 rpm |

(engine only)

- Pressure system Max. 0.5 kg/cm² (7.11 psi)
- Water pump Centrifugal type driven by belt
- Water pump Capacity 740 liters (195.36 gal.)/min at 1,500 rpm (engine)
- Thermostat Wax–pellet type
Opening temp. 77°C
Full open temp. 90°C
- Cooling fan Blower type, iron
1220 mm diameter, 6 blades
- Cooling air flow 15.92 m³ /s

◎ **ELECTRICAL SYSTEM**

- Charging generator 28V×55A
- Voltage regulator Built-in type IC regulator
- Starting motor 24V×11kW
- Battery Voltage 24V
- Battery Capacity 200 AH

- Heat rejection to CAC 32 kcal/sec @1,500 rpm
- Air flow 36 m³/min @1,500 rpm
- Exhaust gas flow 91.8 m³/min @1,500 rpm
- Exhaust gas temp. 600 °C @1,500 rpm
- Max. permissible restrictions
- Intake system 3 kPa initial
6 kPa final
- Exhaust system 6 kPa max.
- Max. permissible altitude 2,000 m
- Fan power 25 kW

◆ **CONVERSION TABLE**

- in. = mm × 0.0394
- PS = kW × 1.3596
- psi = kg/cm² × 14.2233
- in³ = lit. × 61.02
- hp = PS × 0.98635
- lb = kg × 2.20462
- lb/ft = N.m × 0.737
- U.S. gal = lit. × 0.264
- kW = 0.2388 kcal/s
- lb/PS.h = g/kW.h × 0.00162
- cfm = m³/min × 35.336

